


Elbows - ANSI B16.28



Elbows - ANSI B16.9 Short radius- seamless

* An "X" combined with green marking: in stock

* Red marking_ 1 or 2 days



Manufacturing, testing and acceptance to
ASME A234/ASME SA234 GRADE WPB

Norm. Diam. Inch.	Std XS XXS	SCH	D		S		A		theor. Weight 90°		Available in Stock
			mm	inch	mm	inch	mm	inch	kg/ea	lbs/ea	
1"	std		33,4	1,315"	3,4	0,133"	25,4	1"	0,10	0,23	
	XS		33,4	1,315"	4,6	0,177"	25,4	1"	0,14	0,31	
1.1/4"	std		42,2	1,660"	3,6	0,140"	31,8	1.1/4"	0,17	0,38	X
	XS		42,2	1,660"	4,8	0,189"	31,8	1.1/4"	0,23	0,51	
1.1/2"	std		48,3	1,900"	3,7	0,145"	38,1	1.1/2"	0,25	0,55	X
	XS		48,3	1,900"	5,1	0,200"	38,1	1.1/2"	0,39	0,86	X
2"	Std		60,3	2,375"	3,9	0,154"	50,8	2"	0,50	1,10	X
	XS		60,3	2,375"	5,5	0,218"	50,8	2"	0,60	1,33	X
2.1/2"	Std		73	2,875"	5,2	0,203"	63,5	2.1/2"	0,90	1,98	X
	XS		73	2,875"	7	0,276"	63,5	2.1/2"	1,10	2,43	X
3"	Std		88,9	3,500"	5,5	0,216"	76,2	3"	1,40	3,00	X
	XS		88,9	3,500"	7,6	0,300"	76,2	3"	1,80	3,97	X
4"	std		114,3	4,500"	6	0,237"	101,6"	4"	2,70	5,95	X
	XS		114,3	4,500"	8,6	0,337"	101,6"	4"	3,60	7,89	X
5"	std		141,3	5,563"	6,6	0,258"	127	5"	4,50	9,92	X
	XS		141,3	5,563"	9,5	0,357"	127	5"	6,21	13,69	X
6"	std		168,3	6,625"	7,1	0,280"	152,4	6"	6,80	15,00	X
	XS		168,3	6,628"	11	0,432"	152,4	6"	10,30	22,60	X
8"		30	219,1	8,625"	7	0,276"	203,2	8"	11,35	25,00	
	std		219,1	8,625"	8,2	0,322"	203,2	8"	14,00	30,86	X
	XS		219,1	8,625"	12,7	0,500"	203,2	8"	20,70	45,60	X
10"		30	273	10,750"	7,8	0,307"	254	10"	21,35	47,06	
	Std		273	10,750"	9,3	0,365"	254	10"	24,50	54,00	X
	XS		273	10,750"	12,7	0,500"	254	10"	32,90	72,50	X
12"		30	323,9	12,750"	8,4	0,330"	304,8	12"	33,20	73,10	
	std		323,9	12,750"	9,5	0,375"	304,8	12"	36,00	79,50	X
	XS		323,9	12,750"	12,7	0,500"	304,8	12"	47,20	104,00	X
		40	323,9	12,750"	10,3	0,405"	308,4	12"	48,00	105,80	
14"	std		355,6	14,000"	9,5	0,375"	355,6	14"	46,30	102,00	
	XS		355,6	14,000"	12,7	0,500"	355,6	14"	61,20	135,00	
16"	std		406,4	16,000"	9,5	0,375"	406,4	16"	61,30	135,00	
	XS		406,4	16,000"	12,7	0,500"	406,4	16"	80,30	177,00	
18"	std		457,2	18,000"	9,5	0,375"	457,2	18"	78,10	172,00	
	XS		457,2	18,000"	12,7	0,500"	457,2	18"	102,20	225,00	
20"	std		508	20,000"	9,5	0,375"	508	20"	98,10	216,00	
	XS		508	20,000"	12,7	0,500"	508	20"	126,20	278,00	
24"	std		609,6	24,000"	9,5	0,375"	609,6	24"	138,50	305,00	
	XS		609,6	24,000"	12,7	0,500"	609,6	24"	183,40	404,00	