


## Blind Flange 900 Lbs - ANSI B16.5



### Blind Flange, 900 Lbs - ANSI B16.5 Raised Face



Blind

\* An "X" combined with green marking: in stock

\* Red marking: 1 or 2 days

Flanges acc. To ASTM/ASME ANSI B16.5

Norm. diam. inch	D		s		theor. weight		ASTMA 105	ASTMA 350 GR. LF2	ASTMA 182 GR. F316L
	mm	inch	mm	inch	kg/ea	lbs/ea			
<b>1/2"</b>	21,3	0,840"	2,8	0,109"					
<b>3/4"</b>	26,7	1,050"	2,9	0,113"					
<b>1"</b>	33,4	1,315"	3,4	0,133"					
<b>1.1/4"</b>	42,2	1,660"	3,6	0,140"					
<b>1.1/2"</b>	48,3	1,900"	3,7	0,145"					
<b>2"</b>	60,3	2,375"	3,9	0,154"					
<b>2.1/2"</b>	73	2,875"	5,2	0,203"					
<b>3"</b>	88,9	3,500"	5,5	0,216"	13,10	28,88			
<b>4"</b>	114,3	4,500"	6	0,237"	26,90	59,30			
<b>5"</b>	141,3	5,563"	6,6	0,258"	36,50	80,47			
<b>6"</b>	168,3	6,625"	7,1	0,280"	47,40	104,50			
<b>8"</b>	219,1	8,625"	6,4	0,250"	82,50	181,88			
<b>10"</b>	273	10,750"	6,4	0,250"	122,00	268,96			
<b>12"</b>	323,9	12,750"	6,4	0,250"	173,00	381,40			
<b>14"</b>	355,6	14,000"	7,9	0,312"	206,00	454,15			
<b>16"</b>	406,4	16,000"	7,9	0,312"	259,00	570,99			
<b>18"</b>	457,2	18,000"	7,9	0,312"	367,00	809,09			
<b>20"</b>	508	20,000"	9,5	0,375"	463,00	1020,73			
<b>24"</b>	609,6	24,000"	9,5	0,375"	876,00	1931,23			