


Threaded Flange 600 Lbs - ANSI B16.5



Threaded Flange, 600 Lbs - ANSI B16.5 Raised Face

- * An "X" combined with green marking: in stock
- * Red marking: 1 or 2 days



Threaded

Flanges acc. To ASTM/ASME ANSI B16.5

Norm. diam. inch	D		theor. weight		ASTMA 105	ASTMA 350 GR. LF2	ASTMA 182 GR. F316L
	mm	inch	kg/ea	lbs/ea			
1/2"	21,3	0,840"	0,74	1,63			
3/4"	26,7	1,050"	1,27	2,80			
1"	33,4	1,315"	1,52	3,35			
1.1/4"	42,2	1,660"	2,03	4,48			
1.1/2"	48,3	1,900"	2,96	6,53			
2"	60,3	2,375"	3,62	7,98			
2.1/2"	73	2,875"	5,28	11,64			
3"	88,9	3,500"	7,00	15,43			
4"	114,3	4,500"	8,84	19,49			
5"	141,3	5,563"	14,5	31,97			
6"	168,3	6,625"	24,4	53,79			
8"	219,1	8,625"	28,7	63,27			
10"	273	10,750"	43,4	95,68			
12"	323,9	12,750"	70,3	154,98			
14"	355,6	14,000"	84,2	185,63			
16"	406,4	16,000"	98,7	217,59			
18"	457,2	18,000"	173	381,40			
20"	508	20,000"	220	485,01			
24"	609,6	24,000"	312	687,84			