

Socket Weld - ANSI B16.11




Tees (straight) - Black

*AN "X" combined with green marking: in stock

* Red marking: 1 or 2 days

Forgede carbon steel fittings to ASTM A105

Certificates acc. to EN 10204/3.1



| Norm. | 3000 Lbs | | | | Avaliable | Theor. | 6000 Lbs | | | | Avaliable | Theor |
|--------|----------|-------|------|-------|-----------|--------|----------|-------|------|-------|-----------|--------|
| | Diam | A | | B | | | A | | B | | | |
| inch | mm | inch | mm | inch | in | Kg/ea | mm | inch | mm | inch | in | weight |
| | | | | | Stock | | | | | | stock | Kg/ea |
| 1/4" | 20,5 | 4/5 | 22 | 7/8 | | 0,100 | | | | | | |
| 3/8" | 24,5 | 1 | 26,5 | 1 | | 0,155 | | | | | | |
| 1/2" | 28,5 | 1 1/8 | 34 | 1 1/3 | | 0,280 | 28,5 | 1 1/8 | 34 | 1 1/3 | | 0,31 |
| 3/4" | 33,5 | 1 1/3 | 38,5 | 1 1/2 | | 0,370 | 38 | 1 1/2 | 46,5 | 1 5/6 | | 0,86 |
| 1" | 38 | 1 1/2 | 46,5 | 1 5/6 | X | 0,565 | 44,5 | 1 3/4 | 56,5 | 2 2/9 | | 1,45 |
| 1.1/4" | 44,5 | 1 3/4 | 56,5 | 2 2/9 | | 0,870 | 60,5 | 2 3/8 | 76 | 3 | | 2,03 |
| 1.1/2" | 51 | 2 | 62,5 | 2 1/2 | X | 1,280 | | | | | | |
| 2" | 60,5 | 2 3/8 | 76 | 3 | X | 1,790 | 63,5 | 2 1/2 | 92 | 3 5/8 | | 4,43 |
| 2.1/2" | 63,5 | 2 1/2 | 92 | 3 5/8 | | 2,840 | | | | | | |
| 3" | 82,5 | 3 1/4 | 110 | 4 1/3 | | 5,5 | | | | | | |
| 4" | 114,5 | 4 1/2 | 152 | 6 | | 20 | | | | | | |