


Srewed NPT - ANSI B16.11



Unions (F.F) - black/ galvanised

*AN "X" combined with green marking: in stock
 * Red marking: 1 or 2 days

Forgede carbon steel fittings to ASTM A105
 Certificates acc. to EN 10204/3.1



| Norm. | 3000 Lbs | | | | Avaliable in | | Theor. Weight | | 6000 Lbs | | | | Avaliable in stock | Theor weight Kg/ea |
|--------|----------|-------|-----|-------|--------------|--------|---------------|--------|----------|-------|----|-------|--------------------|--------------------|
| | A | | B | | Black | glavan | Black | galvan | A | | B | | | |
| Diam | mm | inch | mm | inch | | | | | mm | inch | mm | inch | | |
| 1/4" | 45 | 1 7/9 | 32 | 1 1/4 | | | 0,140 | | | | | | | |
| 3/8" | 51 | 2 | 38 | 1 1/2 | | | 0,200 | | | | | | | |
| 1/2" | 54 | 2 1/8 | 46 | 1 4/5 | | X | 0,350 | 0,390 | 69 | 2 5/7 | 60 | 2 3/8 | | 0,85 |
| 3/4" | 57 | 2 1/4 | 51 | 2 | | X | 0,425 | 0,47 | | | | | | |
| 1" | 69 | 2 5/7 | 60 | 2 3/8 | | X | 0,650 | 0,720 | | | | | | |
| 1.1/4" | 72 | 2 5/6 | 72 | 2 5/6 | | | 0,975 | 1,07 | | | | | | |
| 1.1/2" | 80 | 3 1/7 | 80 | 3 1/7 | | X | 1,260 | 1,39 | | | | | | |
| 2" | 89 | 3 1/2 | 94 | 3 5/7 | | X | 2,010 | 2,2 | | | | | | |
| 2.1/2" | 114 | 4 1/2 | 122 | 4 4/5 | | X | 5,5 | | | | | | | |
| 3" | 130 | 5 1/8 | 144 | 5 2/3 | | X | 8 | | | | | | | |