		-	
Chequer p	llates -	tear ba	ttern
		eea pa	

DAN	-EOUIP

 \ast An "X" combined with green marking: in stock

* Red marking: 2 or 3 days

* "S+P" marking: Shot blasted and primed

* Tear type acc. to DIN 59222 (EU pattern), tear height 1-2 mm

	Plate dimensions in mm. a x b	Weight	Surface area	Material grades	
	xt	kg/pcs.	m²/pcs.	S 235 JR	S 355 J2
Chequer plates - tear pattern S 235 JR S 355 J2 EN 10025 Certificate: EN 10204/3.1 Tol.: DIN 59220	2000x1000x3,0	52	4,0		
	2000x1000x3,0 S+P	52	4,0		
	2000x1000x5,0	84	4,0		
	2000x1000x5,0 S+P	84	4,0		
	2000x1000x6,0	100	4,0		
	2000x1000x6,0 S+P	100	4,0		
000000	2500x1250x3,0	81	6,3		
	2500x1250x3,0 S+P	81	6,3		
	2500x1250x5,0	131	6,3		
	2500x1250x5,0 S+P	131	6,3		
	2500x1250x6,0	156	6,3		
	2500x1250x6,0 S+P	156	6,3		
Para a a					
2 D D D D D D D D D D D D D D D D D D D	3000x1500x5,0	189	9,0		
	3000x1500x5,0 S+P	189	9,0		
	3000x1500x6,0	225	9,0		
	3000x1500x6,0 S+P	225	9,0		
	3000x1500x8,0	297	9,0		
	3000x1500x8,0 S+P	297	9,0		