

Welding collars (DIN/ISO) - 316L



Welding collars DIN/ISO 316L

* An "X" combined with green marking: in stock

* Red marking: 1 or 2 days

Dimension mm	Wall thickness mm	Available in stock
17,2	2,0	
21,3	2,0	
21,3	3,0	
26,9	2,0	
26,9	3,0	
33,7	2,0	
33,7	3,0	
38,0	2,0	
42,4	2,0	
42,4	3,0	
48,3	2,0	
48,3	3,0	
54,0	2,0	
56,0	3,0	
60,3	2,0	
60,3	3,0	
69,0	2,0	
76,1	2,0	
76,1	3,0	
84,0	2,0	
86,0	3,0	
88,9	2,0	
88,9	3,0	
104,0	2,0	
106,0	3,0	
114,3	2,0	
114,3	3,0	
129,0	2,0	
131,0	3,0	

Dimension mm	Wall thickness mm	Available in stock
139,7	2,0	
139,7	3,0	
154,0	2,0	
156,0	3,0	
168,3	2,0	
168,3	3,0	
204,0	2,0	
206,0	3,0	
219,1	3,0	
254,0	2,0	
256,0	3,0	
273,0	3,0	
306,0	3,0	
323,9	3,0	
356,0	3,0	
406,0	3,0	
508,0	4,0	
609,6	4,0	