

End caps



End caps ANSI B16.9

* An "X" combined with green marking: in stock

* Red marking: 1 or 2 days

Dimensions	Sch	D mm	S mm	h mm	Weight kg	Material	
						304L	316L
1/2"	10 S	21,3	2,11	25,4	0,03		
	40 S STD		2,77		0,04		
3/4"	10 S	26,7	2,11	25,4	0,04		
	40 S STD		2,87		0,05		
1"	10 S	33,4	2,77	38,1	0,09		
	40 S STD		3,38		0,11		
	80 S XS		4,55		0,14		
1.1/4"	10 S	42,2	2,77	38,1	0,11		
	40 S STD		3,56		0,14		
	80 S XS		5,08		0,19		
1.1/2"	10 S	48,3	2,77	38,1	0,13		
	40 S STD		3,68		0,17		
	80 S XS		5,08		0,23		
2"	10 S	60,3	2,77	38,1	0,17		
	40 S STD		3,91		0,23		
	80 S XS		5,54		0,33		
2.1/2"	10 S	73,0	3,05	38,1	0,23		
	40 S STD		5,16		0,39		
3"	10 S	88,9	3,05	50,8	0,37		
	40 S STD		5,49		0,66		
	80 S XS		7,62		0,92		
4"	10 S	114,3	3,05	63,5	0,59		
	40 S STD		6,02		1,17		
	80 S XS		8,56		1,67		
5"	10 S	141,3	3,40	76,2	0,99		
	40 S STD		6,55		1,91		
6"	10 S	168,3	3,40	88,9	1,39		
	40 S STD		7,11		2,90		
	80 S XS		10,97		4,74		
8"	10 S	219,1	3,76	101,6	2,38		
	40 S STD		8,18		5,19		

Dimensions	Sch	D mm	S mm	h mm	Weight kg	304L	316L
10"	10 S	273,1	4,19	127,0	4,14		
	40 S STD		9,27	127,0	9,15		
12"	10 S	323,9	4,57	152,4	6,39		
	40 S STD		9,53	152,4	13,30		
14"	10 S	355,6	4,78	165,1	7,98		
16"	10 S	406,4	4,78	177,8	10,00		
20"	10 S	508,0	5,56	228,6	18,50		
24"	10 / 10 S	609,6	6,35	266,7	30,10		