


Elbows 90 deg. (3S-Radius = D x 1,5) - DIN 2605, St. 35.8/1



Elbows 90 deg. (3S-Radius = D x 1,5)
DIN 2605, St. 35.8/1

* An "X" combined with green marking: in stock

* Red marking: 1 or 2 days



Outside diameter mm D	Wall thickness mm s1	Radius mm	Weight kg	Available in stock
21,3	2,0	28,0	0,040	
	3,2		0,060	
26,9	2,3	28,5	0,060	
	3,2		0,080	
33,7	2,6	38,0	0,120	
	3,2		0,140	
	3,6		0,160	
	4,0		0,170	
38,0	2,6	45,0	0,160	
42,4	2,6	47,5	0,190	
	4,0		0,280	
44,5	2,6	51,0	0,220	
48,3	2,6	57,0	0,260	
	3,6		0,360	
	4,0		0,390	
	4,5		0,440	
	5,0		0,480	
51,0	2,6	63,5	0,310	
57,0	2,9	72,0	0,440	
60,3	2,9	76,0	0,490	
	4,0		0,660	
	4,5		0,740	
	5,0		0,810	
	6,3		1,000	
63,5	2,9	82,5	0,560	
70,0	2,9	92,0	0,690	
76,1	2,9	95,0	0,780	
	4,0		1,060	
	4,5		1,190	
	5,0		1,310	
	5,6		1,450	
	6,3		1,620	

Outside diameter mm D	Wall thickness mm s1	Radius mm	Weight kg	Available in stock
88,9	3,2	114,5	1,220	
	4,5		1,680	
	5,0		1,860	
	5,6		2,070	
	6,3		2,310	
101,6	3,6	133,5	1,820	
108,0	3,6	142,5	2,070	
114,3	3,6	152,5	2,350	
	4,5		2,920	
	5,6		3,600	
	6,3		4,020	
	7,1		4,500	
	8,8		5,460	
133,0	4,0	181,0	3,620	
139,7	4,0	190,5	4,010	
	5,0		4,970	
	6,3		6,200	
	8,0		7,780	
	10,0		9,570	
159,0	4,5	216,0	5,820	
	7,1		9,020	
168,3	4,5	228,5	6,520	
	5,6		8,060	
	7,1		10,100	
	8,8		12,400	
193,7	5,6	270,0	10,600	
	8,0		15,500	
219,1	6,3	305,0	15,800	
	12,5		30,500	
244,5	6,3	340,0	19,800	
273,0	6,3	381,0	24,800	
323,9	7,1	457,0	39,800	
355,6	8,0	533,5	57,500	
406,4	8,8	609,5	82,600	
457,0	10,0	686,0	119,000	
508,0	11,0	762,0	161,000	