Socket Welding Flange 300 Lbs - ANSI B16.5

Socket Welding Flange, 300 Lbs - ANSI B16.5
Raised Face

* An "X" combined with green marking: in stock
* Red marking: 1 or 2 days

Flanges acc. To ASTM/ASME ANSI B16.5



Socket Welding (1/2" to 3" only)

Norm. diam. inch	Sch	D mm	D inch	B mm	B inch	B1 mm	B1 inch	theor. weight kg/ea	theor. weight lbs/ea	ASTMA 105	ASTMA 350 GR. LF2	ASTMA 182 GR. F316L
1/2"	Std XS XXS	21,3	0,840"	22,40	0,883	15,7	0,619	0,66	1,46			
3/4"	Std XS XXS	26,7	1,050"	27,70	1,091	20,8	0,820	0,59	1,30			
1"	Std XS XXS	33,4	1,315"	34,50	1,359	26,7	1,052	0,81	1,79			
1.1/4"	Std XS XXS	42,2	1,660"	43,20	1,702	35,1	1,383	1,07	2,36			
1.1/2"	Std XS XXS	48,3	1,900"	49,50	1,950	40,9	1,611	1,36	3,00			
2"	Std XS XXS	60,3	2,375"	62,00	2,443	52,6	2,072	2,10	4,63			
2.1/2"	Std XS XXS	73	2,875"	74,70	2,943	62,7	2,470	4,4	9,70			
3"	Std XS XXS	88,9	3,500"	90,70	3,574	78	3,073	5,92	13,05			