

EN 1092-1 type 05 - blind flange PN 25



Type 05, blind flange PN 25

*AN "X" combined with green marking: in stock

* Red marking: 1 or 2 days



Flanges acc. to EN 1092-1

DN	Outside diameter of pipe		Bore diameters		Theor. Wiegth kg/ea	P 250 GH	316-L 1 4404	316Ti 1 4571
	mm	inch	mm	inch				
	A		B					
10	17,2	0,68	NA	NA				
15	21,3	0,84	NA	NA				
20	26,9	1,06	NA	NA				
25	33,7	1,33	NA	NA				
32	42,4	1,67	NA	NA				
40	48,3	1,90	NA	NA				
50	60,3	2,38	NA	NA				
65	76,1	3,00	NA	NA				
80	88,9	3,50	NA	NA				
100	114,3	4,50	NA	NA				
125	139,7	5,50	NA	NA				
150	168,3	6,63	NA	NA				
200	219,1	8,63	NA	NA				
250	273,0	10,76	NA	NA				
300	323,9	12,76	NA	NA				
350	355,6	14,01	NA	NA				
400	406,4	16,01	NA	NA				
450	457,0	18,01	NA	NA				
500	508,0	20,02	NA	NA				
600	610,0	24,03	NA	NA				