


EN 1092-1 type 11 - Welding neck PN 25



Type 11, Welding neck PN 25

*AN "X" combined with green marking: in stock

* Red marking: 1 or 2 days



Flanges acc. to EN 1092-1

| DN | Outside diameter of pipe | | Bore diameters | | Theor. Wiegth kg/ea | P 250 GH | 316-L 1 4404 | 316Ti 1 4571 |
|-----|--------------------------|-------|----------------|-------|------------------------|----------|-----------------|-----------------|
| | mm | inch | mm | inch | | | | |
| | A | | B | | | | | |
| 10 | 17,2 | 0,68 | 13,2 | 0,52 | | | | |
| 15 | 21,3 | 0,84 | 17,3 | 0,68 | | | | |
| 20 | 26,9 | 1,06 | 22,3 | 0,88 | | | | |
| 25 | 33,7 | 1,33 | 28,5 | 1,12 | | | | |
| 32 | 42,4 | 1,67 | 37,2 | 1,47 | | | | |
| 40 | 48,3 | 1,90 | 43,1 | 1,70 | | | | |
| 50 | 60,3 | 2,38 | 54,5 | 2,15 | | | | |
| 65 | 76,1 | 3,00 | 70,3 | 2,77 | | | | |
| 80 | 88,9 | 3,50 | 82,5 | 3,25 | | | | |
| 100 | 114,3 | 4,50 | 107,1 | 4,22 | | | | |
| 125 | 139,7 | 5,50 | 131,7 | 5,19 | | | | |
| 150 | 168,3 | 6,63 | 159,3 | 6,28 | | | | |
| 200 | 219,1 | 8,63 | 206,5 | 8,14 | 17,1 | | | |
| 250 | 273,0 | 10,76 | 258,8 | 10,20 | 24,3 | | | |
| 300 | 323,9 | 12,76 | 307,9 | 12,13 | 31,8 | | | |
| 350 | 355,6 | 14,01 | 339,6 | 13,38 | 48,8 | | | |
| 400 | 406,4 | 16,01 | 388,8 | 15,32 | 63,3 | | | |
| 450 | 457,0 | 18,01 | 439,4 | 17,31 | 76,0 | | | |
| 500 | 508,0 | 20,02 | 488,0 | 19,23 | 97,0 | | | |
| 600 | 610,0 | 24,03 | 588,0 | 23,17 | 121,0 | | | |