


Screwed NPT -ANSI B16.11



Hex. Bushings- black/galvanised- 3000 Lbs

*AN "X" combined with green marking: in stock

* Red marking: 1 or 2 days



Forgede carbon steel fittings to ASTM A105

Certificate acc. To EN 10204 3.1

Norm. diam inch	A		B		Delivery prog.		Theor. Weight in kg/ea	
	mm	inch	mm	inch	Black	galvan	black	galvan
1/4" x 1/8"	14,3	0,56	17,6	0,69			0,027	0,027
3/8" x 1/8"	25,5	1,00	19	0,75			0,027	0,027
3/8" x 1/4"	25,5	1,00	19	0,75			0,027	0,027
1/2" x 3/8"	28	1,10	22	0,87			0,040	0,040
1/2" x 1/4"	28	1,10	22	0,87			0,055	0,055
3/4" x 1/2"	31,5	1,24	27	1,06			0,085	0,085
3/4" x 1/4"	31,5	1,24	27	1,06			0,120	0,120
3/4" x 3/8"	31,5	1,24	27	1,06			0,070	0,070
1" x 3/4"	34,5	1,36	35	1,38			0,105	0,105
1" 1/2"	34,5	1,36	35	1,38			0,150	0,150
1" x 3/8"	34,5	1,36	35	1,38			0,170	0,170
1" x 1/4"	34,5	1,36	35	1,38			0,190	0,190
1.1/4" x 1"	41,5	1,64	46	1,81			0,215	0,215
1.1/4" x 3/4"	41,5	1,64	46	1,81			0,235	0,235
1.1/4" x 1/2"	41,5	1,64	46	1,81			0,235	0,235
1.1/2" x 1.1/4"	43	1,69	50	1,97			0,360	0,360
1.1/2" x 1"	43	1,69	50	1,97			0,380	0,380
1.1/2" x 3/4"	43	1,69	50	1,97			0,430	0,047
1.1/2" x 1/2"	43	1,69	50	1,97			0,505	0,550
2" x 1/2"	46	1,81	63	2,48			0,900	0,965
2" x 3/4"	46	1,81	63	2,48			0,750	0,750
2" x 1.1/2"	46	1,81	63	2,48			0,470	0,470
2" x 1"	46	1,81	63	2,48			0,815	0,815
3" x 2"	38,8	1,53	88,9	3,5			1,445	1,590
4" x 3"	44,5	1,75	117,4	4,63			3,000	3,250