

Socket weld - ANSI B16.11




Reducing inserts - balck - 3000 Lbs

*AN "X" combined with green marking: in stock

* Red marking: 1 or 2 days

Forgede carbon steel fittings to ASTM A105

Certificates acc. to EN 10204/3.1



Norm. Diam	A		B		Available in	Theor. Weight
inch	mm	inch	mm	inch	Stock	Kg/ea
1/2" x 1/4"	25	1	21,6	6/7		0,050
1/2" x 3/8"	33,5	1 1/3	21,6	6/7		0,070
3/4" x 1/2"	35,5	1 2/5	26,9	1		0,125
1" x 1/2"	33,5	1 1/3	33,6	1 1/3		0,175
1" x 3/4"	41,5	1 5/8	33,6	1 1/3		0,190
1.1/2" x 1/2"	35,5	1 2/5	48,5	2		0,380
1.1/2" x 3/4"	35	1 3/8	48,5	2		0,350
1.1/2" x 1"	36,5	1 4/9	48,5	2		0,350
2" x 1/2"	38	1 1/2	60,3	2 3/8		0,600
2" x 3/4"	39,6	1 5/9	60,3	2 3/8		0,650
2" x 1"	38	1 1/2	60,3	2 3/8		0,600
2" x 1.1/2"	40	1 4/7	60,3	2 3/8		0,480