


Gasket Dimension




PN 6-40



For raised face flanges (RF) as per DIN 2690

DN	d1	PN 6	PN 10	PN 16	PN 25	PN 40	
		d2					
6	10	28	38	38	38	38	
8	14	33	43	43	43	43	
10	18	38	45	45	45	45	
15	22	43	50	50	50	50	
20	28	53	60	60	60	60	
25	35	63	70	70	70	70	
32	43	75	82	82	82	82	
40	49	85	92	92	92	92	
50	61	95	107	107	107	107	
65	77	115	127	127	127	127	
80	90	132	142	142	142	142	
100	115	152	162	162	168	168	
125	141	182	192	192	195	195	
150	169	207	218	218	225	225	
175	195	237	248	248	255	267	
200	220	262	273	273	285	292	
250	274	318	328	330	342	353	
300	325	373	378	385	402	418	
350	368	423	438	445	458	475	
400	420	473	490	497	515	547	
450	470	528	540	557	565	572	
500	520	578	595	618	625	628	
600	620	680	695	735	730	745	
700	720	785	810	805	830	850	
800	820	890	915	910	940	970	
900	920	990	1015	1010	1040	1080	
1000	1020	1090	1120	1125	1150	1190	
1200	1220	1305	1340	1340	1360	1395	
1400	1420	1520	1545	1540	1575	1615	
1600	1620	1720	1770	1760	1795	1830	

For raised face flanges (RF) as per ASME B16.11



DN	d1	150 lbs	300 lbs	400 Lbs	600 Lbs	900 Lbs	1500 Lbs
		d2					
15	21	48	54	54	54	64	64
20	27	57	67	67	67	70	70
25	33	67	73	73	73	79	79
32	42	76	83	83	83	89	89
40	48	86	95	95	95	98	98
50	60	105	111	111	111	143	143
65	73	124	130	130	130	165	165
80	89	136	149	149	149	168	171
90	102	162	165	165	165		
100	114	175	181	178	194	206	210
125	141	197	216	213	241	248	254
150	168	222	251	248	267	289	283
200	219	279	308	305	321	359	352
250	273	340	362	359	400	435	435
300	324	410	422	419	457	498	520
350	356	450	486	483	492	520	580
400	406	515	540	535	565	575	640
450	457	550	595	595	615	640	705
500	510	605	655	650	685	700	755
550	559	660	705	702	733		
600	610	715	775	770	790	840	900