






Steel - Square holes / trefoil

St.12.03 StW 22 St. 37.2	Hulmønster Din 24 042			Luft %	1000 x 2000 Plade tykkelse i mm				1250 x 2500 Plade tykkelse i mm			1500 x 3000 Plade tykkelse i mm		
	Qg	F	KD											
Firkantede- huller Kvadratdeling 	Qg	3,00	5,00	36	0,75				0,75					
	Qg	5,00	8,00	39	1,00	1,50								
	Qg	5,00	7,50	45	0,75	1,00	1,50	2,00	1,00	1,50	2,00			
	Qg	5,00	7,00	51	0,80	1,00	1,50	2,00	1,00					
	Qg	5,50	9,00	47	1,00									
	Qg	6,00	9,00	44	1,50									
	Qg	8,00	12,00	44	1,00	1,50	2,00							
	Qg	8,00	11,00	53	1,00									
	Qg	8,00	10,00	64	1,00	1,50								
	Qg	9,00	38,00	5	1,50									
	Qg	9,00	34,00	7	1,50	2,00								
	Qg	10,00	15,00	44	1,00	1,50	2,00	3,00						
	Qg	10,00	14,00	51	1,00	1,50	2,00	3,00	1,00	1,50	2,00			
	Qg	10,00	12,00	70	1,00	1,50	2,00							
	Qg	15,00	20,00	56	2,00									
	Qg	20,00	25,00	64	1,50	3,00								
	Qg	25,00	35,00	51	3,00									
	Firkantede- huller Forsatte 	Hulmønster Din 24 042			Luft %	1000 x 2000 Plade tykkelse i mm				1250 x 2500 Plade tykkelse i mm			1500 x 3000 Plade tykkelse i mm	
Qv		F	KD											
Qv	8,00	12,00	44	2,00										
Kløverblad 	Hulmønster			Luft %	1000 x 2000 Plade tykkelse i mm				1250 x 2500 Plade tykkelse i mm			1500 x 3000 Plade tykkelse i mm		
	Nr.													
	6				44	1,00								
20			47	1,00	1,50	2,00		1,00	1,50	2,00				