







## Galvanized, round square holes

Runde huller Triangeldeling	Hulmønster Din 24 041			Luft %	1000 x 2000 Plade tykkelse i mm			1250 x 2500 Plade tykkelse i mm	1500 x 3000 Plade tykkelse i mm			
	Rv	Ø	TD									
	Rv	1,50	3,00	23	0,80							
	Rv	2,00	3,50	30	1,00							
	Rv	2,00	3,00	40	0,80	1,00						
	Rv	3,00	5,00	33	1,00	1,50						
	Rv	4,00	6,00	40	1,00							
	Rv	5,00	8,00	35	1,00	1,50	2,00					
	Rv	8,00	12,00	40	2,00							
	Rv	10,00	15,00	40	1,50	2,00	3,00					
	Rv	15,00	20,00	51	3,00							
Firkantede- huller Kvadratdeling	Hulmønster Din 24 042			Luft %	1000 x 2000 Plade tykkelse i mm			1250 x 2500 Plade tykkelse i mm	1500 x 3000 Plade tykkelse i mm			
	Qg	F	KD									
	Qg	5,00	7,50		45	0,80	1,00			1,50	2,00	
	Qg	8,00	12,00		44	2,00						
Qg	10,00	12,00	70	1,00	2,00		2,00					
												
Firkantede- huller Diagonaldeling	Hulmønster Din 24042			Luft %	1000 x 2000 Plade tykkelse i mm			1250 x 2500 Plade tykkelse i mm	1500 x 3000 Plade tykkelse i mm			
	Qv	F	DD									
	Qv	8,00	17,00	44	1,50							
Aflange huller Forsatte på langs	Hulmønster Din 24 043			Luft %	1000 x 2000 Plade tykkelse i mm			1250 x 2500 Plade tykkelse i mm	1500 x 3000 Plade tykkelse i mm			
	Lv	B	L									
	Lv	5,00	25,00	50	1,50							