


I-Beams HE serie A



- * From stock: 6 m length
- * An "X" combined with green marking: in stock
- * **Red** marking: 1 or 2 days

| | Profile no. | Dimensions in mm. | | | | Surface area m ² /m | Weight kg/m | Material grades | |
|--|-------------|-------------------|------|------|------|-----------------------------------|----------------|-----------------|------|
| | | h | b | d | t | | | S235 | S355 |
| I-Beams HE serie A S 235 JR S 355 J2 + AR EN 10025 Tol. EN 10034 Certificate: EN 10204/3.1  | 100 | 96 | 100 | 5,0 | 8,0 | 0,56 | 16,7 | | X |
| | 120 | 114 | 120 | 5,0 | 8,0 | 0,68 | 19,9 | | X |
| | 140 | 133 | 140 | 5,5 | 8,5 | 0,79 | 24,7 | | X |
| | 160 | 152 | 160 | 6,0 | 9,0 | 0,91 | 30,4 | | X |
| | 180 | 171 | 180 | 6,0 | 9,5 | 1,02 | 35,5 | | X |
| | 200 | 190 | 200 | 6,5 | 10,0 | 1,14 | 42,3 | | X |
| | 220 | 210 | 220 | 7,0 | 11,0 | 1,26 | 50,5 | | X |
| | 240 | 230 | 240 | 7,5 | 12,0 | 1,37 | 60,3 | | |
| | 260 | 250 | 260 | 7,5 | 12,5 | 1,48 | 68,2 | | |
| | 280 | 270 | 280 | 8,0 | 13,0 | 1,60 | 76,4 | | |
| | 300 | 290 | 300 | 8,5 | 14,0 | 1,72 | 88,3 | | |
| | 320 | 310 | 300 | 9,0 | 15,5 | 1,76 | 97,6 | | |
| | 340 | 330 | 300 | 9,5 | 16,5 | 1,79 | 105 | | |
| | 360 | 350 | 300 | 10,0 | 17,5 | 1,83 | 112 | | |
| | 400 | 390 | 300 | 11,0 | 19,0 | 1,91 | 125 | | |
| | 450 | 440 | 300 | 11,5 | 21,0 | 2,01 | 140 | | |
| | 500 | 490 | 300 | 12,0 | 23,0 | 2,11 | 155 | | |
| | 550 | 540 | 300 | 12,5 | 24,0 | 2,21 | 166 | | |
| | 600 | 590 | 300 | 13,0 | 25,0 | 2,31 | 178 | | |
| | 650 | 640 | 300 | 13,5 | 26,0 | 2,41 | 190 | | |
| 700 | 690 | 300 | 14,5 | 27,0 | 2,50 | 204 | | | |
| 800 | 790 | 300 | 15,0 | 28,0 | 2,70 | 224 | | | |
| 900 | 890 | 300 | 16,0 | 30,0 | 2,90 | 252 | | | |
| 1000 | 990 | 300 | 16,5 | 31,0 | 3,10 | 272 | | | |