


I-Beams HE serie A



- * From stock: 6 m length
- * An "X" combined with green marking: in stock
- * **Red** marking: 1 or 2 days

	Profile no.	Dimensions in mm.				Surface area m ² /m	Weight kg/m	Material grades	
		h	b	d	t			S 235	S 355
I-Beams HE serie A S 235 JR S 355 J2 + AR EN 10025 Tol. EN 10034 Certificate: EN 10204/3.1 	100	96	100	5,0	8,0	0,56	16,7		X
	120	114	120	5,0	8,0	0,68	19,9		X
	140	133	140	5,5	8,5	0,79	24,7		X
	160	152	160	6,0	9,0	0,91	30,4		X
	180	171	180	6,0	9,5	1,02	35,5		X
	200	190	200	6,5	10,0	1,14	42,3		X
	220	210	220	7,0	11,0	1,26	50,5		
	240	230	240	7,5	12,0	1,37	60,3		X
	260	250	260	7,5	12,5	1,48	68,2		
	280	270	280	8,0	13,0	1,60	76,4		
	300	290	300	8,5	14,0	1,72	88,3		
	320	310	300	9,0	15,5	1,76	97,6		
	340	330	300	9,5	16,5	1,79	105		
	360	350	300	10,0	17,5	1,83	112		
	400	390	300	11,0	19,0	1,91	125		
	450	440	300	11,5	21,0	2,01	140		
	500	490	300	12,0	23,0	2,11	155		
	550	540	300	12,5	24,0	2,21	166		
	600	590	300	13,0	25,0	2,31	178		
	650	640	300	13,5	26,0	2,41	190		
700	690	300	14,5	27,0	2,50	204			
800	790	300	15,0	28,0	2,70	224			
900	890	300	16,0	30,0	2,90	252			
1000	990	300	16,5	31,0	3,10	272			