


## I-Beams HE serie B



- \* From stock: 6 m length
- \* An "X" combined with green marking: in stock
- \* Red marking: 1 or 2 days

	Profile no.	Dimensions in mm.				Surface area m <sup>2</sup> /m	Weight kg/m	Material grades	
		h	b	d	t			S 235	S 355 J2+N
<b>I-Beams HE serie B</b> S 235 JR S 355 J2 + AR EN 10025 Tol. EN 10034 Certificate: EN 10204/3.1  	100	100	100	6,0	10,0	0,57	20,4		X
	120	120	120	6,5	11,0	0,69	26,7		X
	140	140	140	7,0	12,0	0,81	33,7		X
	160	160	160	8,0	13,0	0,92	42,6	X	X
	180	180	180	8,5	14,0	1,04	51,2		X
	200	200	200	9,0	15,0	1,15	61,3		X
	220	220	220	9,5	16,0	1,27	71,5		X
	240	240	240	10,0	17,0	1,38	83,2		
	260	260	260	10,0	17,5	1,50	93,0		
	280	280	280	10,5	18,0	1,62	103		
	300	300	300	11,0	19,0	1,73	117		X
	320	320	300	11,5	20,5	1,77	127		
	340	340	300	12,0	21,5	1,81	134		X
	360	360	300	12,5	22,5	1,85	142		
	400	400	300	13,5	24,0	1,93	155		
	450	450	300	14,0	26,0	2,03	171		
	500	500	300	14,5	28,0	2,12	187		
	550	550	300	15,0	29,0	2,22	199		
	600	600	300	15,5	30,0	2,32	212		
	650	650	300	16,0	31,0	2,42	225		
700	700	300	17,0	32,0	2,52	241			
800	800	300	17,5	33,0	2,71	262			
900	900	300	18,5	35,0	2,91	291			
1000	1000	300	19,0	36,0	3,11	314			